



BRICKFORM® Overlay Liquid Colorant™

Integral Color for BRICKFORM Overlay Products (excluding OL-60)

PRODUCT DESCRIPTION • BRICKFORM Overlay Liquid Colorant is an engineered blend of color admixtures for the BRICKFORM Stampable Overlay, Micro-Topping and SM Professional Grade product lines. BRICKFORM Overlay Liquid Colorant is UV resistant and manufactured to strict standards to ensure color uniformity and consistency. BRICKFORM Overlay Liquid Colorants are non-hazardous water-based formulations providing easy clean up and no hassle shipping. BRICKFORM Overlay Liquid Colorant is available in 39 standard colors, packaged in 10 oz. bottles. See the BRICKFORM Standard Color Selection Guide for a complete list of available colors (excluding Smokey Blue).

BASIC USES

BRICKFORM Overlay Liquid Colorant is designed specifically as liquid colorant admixtures for coloring BRICKFORM's Stampable Overlay (SC-60 only), Micro-Topping and SM Professional Grade product lines.

MIXING

BRICKFORM Overlay Liquid Colorants are formulated as a one-to-one mixing ratio. Mix one bottle of BRICKFORM Overlay Liquid Colorant with one unit of BRICKFORM Stampable Overlay, Micro-Topping or SM Professional Grade. Liquid colorant is mixed with the liquid polymer before adding the dry grout mix. Refer to BRICKFORM Technical Data Sheets for all products prior to use.

SEALING

After the concrete has been allowed to cure for 28 days, protect the surface with BRICKFORM Gem-Seal, Poly-Astic, Poly-Seal, Safety-Seal, or Satin-Seal. Please get a copy of the appropriate Technical Information and Material Safety Data Sheet before attempting to use these products. Once sealed, protect the surface from foot traffic for 24 hours and vehicular traffic for 5 days.

COLOR SELECTION

BRICKFORM Overlay Liquid Colorant: Standard Color Selection Guide (excluding Smokey Blue)

PACKAGING

10 oz. bottle, 6 units per case, 48 cases per pallet.

STORAGE AND SHELF LIFE

Store in cool, dry location. Keep containers tightly sealed. Do not allow products to freeze. Shelf life of properly stored materials is 12 months from date of manufacture in unopened original packaging.

CLEAN UP

While BRICKFORM Overlay Liquid Colorant is still wet, it can be removed from tools with clean water.

LIMITATIONS

Minimum ambient and surface temperature for application is 40° F (4° C) during application and for a minimum of 24 hours after application. Do not apply if rain is expected during application or within 24 hours after application. Variations in ambient and surface temperature, mixing techniques and finishing techniques will affect final appearance. Samples and mock-ups are strongly recommended.

PRECAUTIONS

Read the Material Safety Data Sheet before use or handling. It is mandatory to take the following precautions to protect workers and the public:

KEEP OUT OF THE REACH OF CHILDREN.

Keep away from excessive heat and open flame.

Avoid inhalation of vapors. Ensure adequate ventilation.

Avoid contact with skin. Protective clothing is recommended.

Contact areas should be thoroughly washed with soap and water.

Avoid contact with eyes. Flush eyes with water if contact occurs.

Avoid ingestion of material. If ingestion occurs, contact a poison control center or physician.

Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet.

WARRANTY

This product is not intended for public use and is intended for use by trained, professional contractors and installers. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

MANUFACTURER

BRICKFORM, A Division of Solomon Colors, Inc.

ORDER SPECIFICATIONS

E-Stain

Shipping Weight
1 lb

Container Size
10 oz.

MTC-100	DARK GREY	MTC-1080	ADOBE BUFF	MTC-500	TILE RED
MTC-1010	SMOKEY BEIGE	MTC-1090	SUN BUFF	MTC-515	SUNBAKED CLAY
MTC-1015	BLUSH BEIGE	MTC-115	VENETIAN PINK	MTC-525	DUSTY ROSE
MTC-1020	ANTIQUER ROSE	MTC-200	MEDIUM GREY	MTC-550	BRICK RED
MTC-1030	ASH WHITE	MTC-250	OYSTER WHITE	MTC-575	VICTORIAN RED
MTC-1035	SUMMER BEIGE	MTC-300	NUTMEG	MTC-600	LIGHT GREY
MTC-1040	WEATHERED SAGE	MTC-310	CREAM BEIGE	MTC-615	STONE GREY
MTC-1045	SHADOW SLATE	MTC-320	GOLDEN SANDSTONE	MTC-625	DOVER BLUE
MTC-1050	ANTIQUER CORK	MTC-325	SANDSTONE	MTC-700	TERRA COTTA
MTC-1055	PECOS SAND	MTC-330	COCONUT	MTC-735	CAPPUCCINO
MTC-1065	QUARRY RED	MTC-350	DESERT TAN	MTC-810	WALNUT
MTC-1070	SANDY BUFF	MTC-375	BUFF TAN	MTC-820	MUTED GREEN
MTC-1075	ROSE TAUPE	MTC-425	AUTUMN BROWN	MTC-825	SLATE GREEN